MATERIALS HANDLING SYSTEMS











Heavy Duty Slider Bed Conveyors HSC .

The synthetic belt slides over a solid stationary bed. HSC Conveyors are low cost heavy duty conveyors capable of transporting medium loads (20-50 Kg/m) over distances of up to 30 meters. They can be manufactured in Stainless Steel , and fitted with FDA approved belting and can be floor mounted, suspended from ceilings using hangers, or wall mounted using brackets .

ᡉ سيور منزلقة على الواح HSC .

تستخدم للأحمال المتوسطة من ٢٠ الى ٥٠ كجم/متر طولى لمسافات تصل الى ٣٠ متر حيث تنزلق الحصائر على الواح من الصلب كما يمكن ان تصنع من صلب لايصدأ للأغراض الصحية والغذائية. يمكن ايضا تحميلها على ارجل ارضية او كوابيل حوائط او تعليقها من الاسقف.

Factory :New Borg El Arab 2nd Zone entrance 2c street 3 - entrance 2c street 5 Tel:+20-(03)-4624127 - 4624126 - 4624025 fax : (03) 4624291 Cairo Office : Corniche El Nile, Maadi, Cairo Tel +20:(0)2-25266333 Fax +20:(0)2-25264888



www.UnitelEgypt.com

Info@UnitelEgypt.com

Sales@UnitelEgypt.com

HSC Heavy Duty Slider Bed Conveyor

Features

This type of conveyor is a general purpose conveyor where the synthetic belt slides over a solid stationary bed. The sheet metal construction of this conveyor is rigid and offers a stable chassis on which head and tail pulleys are mounted.

Characteristics

The HSC family of conveyors accepts many accessories which makes it a very flexible and versatile building block.

It can be fitted with hoppers, chutes, belt troughing attachments, side tables, inverters for variable belt speed. The belts can be standard PVC types, food grade types, cleated with corrugated sides for steep angle elevators, or grip-face type for inclined applications.

This family is compatible with the Gravity Roller Conveyor family RLG.

Applications

HSC Conveyors are low cost heavy duty conveyors capable of transporting medium loads (20-50 Kg/m) over distances of up to 12 meters.

They are used in general purpose transportation of a great variety of unit goods, of any size and shape, in chemical, engineering, food, process, and pharmaceutical industries.

HSC conveyors can also be manufactured in Stainless Steel for applications in food processing, or wet environment, and fitted with FDA approved belting.

HSC conveyors can be floor mounted, suspended from ceilings using hangers, or wall mounted using brackets

www.UnitelEgypt.com








HSC Heavy Duty Slider Bed Conveyor

Specifications



| Loading Capacity | 200 to 500 N/m |
|-------------------------|--|
| Head Pulley Diameter | Ø168 |
| Take Up Pulley Diameter | Ø100,168 |
| Return Rollers Diameter | Ø50 |
| Return Rollers Pitch | 1215 , 2430 mm |
| Linear Speed | Sprocket driven 18, 23, 28, direct drive 28,33, m/min |
| Mains Supply | 380VAC 50 Hz 3phase |
| Motor Power | Calculated based upon belt loading and conveyor length |
| Motor Class | IP54 |
| Insulation Class | IP54 |
| Belt Materials | PVC, PU, Cleated |
| Take-up Distance | 120mm |
| Paint | Electrostatic Epoxy Powder RAL 7035 |

| | | | Dimensions | | | |
|---------------|-----------------|----------------|----------------|---------------|---------------|-----|
| Standard Wid | th (W) / Pref | ferred Values | | | | |
| Outer Distanc | e (Wo) | | | | | |
| W | 300 | 400 | 500 | 600 | 700 | 800 |
| Wo | 386 | 486 | 586 | 686 | 786 | 886 |
| Standard Sect | ion Length : | 2430 | | | | |
| Options : in | ntermediate ler | ngths availabl | e (in 90 mm i | ncrements on | ly) | |
| Modules are a | ttached togeth | er using Butt | Couplings, to | obtain any de | sired length. | |

www.UnitelEgypt.com

HSC Heavy Duty Slider Bed Conveyor

| | Op | tions | |
|----------------------------|------|-------------------------------|------------|
| Floor Supports | SGL | | |
| | Yes | | |
| Ceiling Hangers | | Overhead Drive | Var |
| Wall Mount | Yes | | Yes |
| Head pulley lagging | Yes | Left or Right Side Drive | Yes |
| V-Belt Underside Guide | Yes | Brake Motor | Yes Yes |
| Grip Face Belt Material | Yes | Bidirectional motion | |
| Cleated Belts | Yes | Variable Speed Drives | |
| Corrugated Belt Sides | Yes | Stainless Steel Construction | |
| Accumulation Belt | Yes | | |
| Material (PU) | 105 | | |
| | Acce | essories | |
| | | | |
| Long-span Under-Trussing | Yes | Inside scraper | Yes |
| Cross Bracing | | Outside Scrapers | Yes |
| Butt Coupling Yes | | Emergency Pull Cord | Yes |
| Nose Wheel | Yes | Brake Rollers | No |
| Front Bumper | Yes | | |
| Tail Bumper | Yes | | |
| End Stops | Yes | Troughing Attachment. | Yes |
| Deflector | Yes | Optical Switches and Controls | Yes |
| Drip Pan | Yes | | |
| Chutes | No | Push Button Station | Yes |
| Guard Rails Y | | Pushers | Yes |
| Side Skirts Ye | | Back Stops | No |
| Feed (Tail end) Hopper | Yes | | |
| Delivery (Head end) Hopper | Yes | Longitudinal Side Tables | Yes |
| Head Pulley Hood | No | Individual Side Tables | Yes |

مكتب القاهرة : برج القانونيين كورنيش المعادى تليفون : ٢/٢٥٢٦٦٣٣٣ • فاكس : ٢/٢٥٢٦٤٨٨٨ •

مدينة برج العرب الجديدة – المنطقة الصناعية الثانية يونيتل/ مدخل ٢ج شارع٣- مدخل ٢ج شارع٥ تليفون : ٣/٤٦٢٤-٤٦٢٤٦-٤٦٢٤١٢٦-٤٦٢٤٤٢٤-٠٣ فاكس : ٣/٤٦٢٤٢٩٩٠،



www.UnitelEgypt.com



Sales@UnitelEgypt.com

Info@UnitelEgypt.com